

# FW-5015

Fire Rated Access Door,  
*Recessed for Drywall walls*

### Application

- For installation in drywall walls requiring concealing of the door panel consistent to surroundings
- For use in walls, fire-rated for up to 90-minutes with a temperature rise of max 250° C (450°F) over 30 minutes

### Product Features

- Recessed reinforced insulated door fitted with 5/8" Fire-rated drywall.
- Concealed hinge & self-centering device ensures seamless appearance in walls
- Self-closing & self-latching door mechanism
- Perforated Frame ensures trouble-free application of skim coat to edge of the door
- Zinc coated steel provides superior corrosion resistance
- Testing standards UL 10(b) and ULC S104

### FW-5015 Access Door Specifications:

Door: Steel-22 Gauge recessed fitted with 5/8" thick drywall suitable to accept skim coat finish on site.

Door Frame: Steel-22 Gauge press bent for strength and rigidity with pre-punched flanges for convenient mounting and accepting skim coat finish on site

Hinge: Concealed

Fire Rating (Walls): Meets 1½ hour fire rating requirement in accordance with UL 10(b) and CAN/ULC S104-10 for max size upto 24" x 36"

Latch: Self-latching bolt, operated by flush key

Finish: Satin coat steel

### FW-5015 STANDARD SIZES

*(other sizes available upon request)*

| Nominal Door Size W&H |           | Latches | Weight per Door |      |
|-----------------------|-----------|---------|-----------------|------|
| Inches                | mm        |         | lbs.            | kg.  |
| 12 X 12               | 305 X 305 | 1       | 10              | 4.5  |
| 16 x 16               | 406 X 406 | 1       | 14              | 6.4  |
| 18 X 18               | 457 x 457 | 1       | 18              | 8.2  |
| 24 X 24               | 610 x 610 | 1       | 29              | 13.1 |
| 24 X 36               | 610 X 914 | 2       | 42              | 19.0 |

Wall opening is W + 3/8" ( 9 mm)

For detailed specifications see submittal sheet

**PATENT PENDING**



**PATENT PENDING**

