

# SD-6000

## SECURITY DOORS Heavy Security Access Door

### Application

- Installation ideal for prisons, correctional facilities, housing projects etc.
- Heavy duty access door designed for use in high security areas

### Product Features

- 10 Gauge Door
- Security butt hinges are surface welded to the door and frame
- A detention type deadbolt lock with paracentric key is standard

### SD-6000 Access Door Specifications:

**Door / Door Frame:** Door 10 gauge (.134) plate & frame is 2x2x3/16 angle, flush to edge of frame. Mounting frame to have anchor straps

**Hinge:** Heavy duty butt hinges, welded to door and frame

**Standard Latch:** Detention type deadbolt lock with paracentric key

**Optional Latches/Locks:** Tamperproof security cam latches, cylinder lock and key. When master keying is required, doors can be prepared for rim or mortise cylinder locks


**Finish:** 5 stage iron phosphate preparation with prime coat of White alkyd baked-on enamel. Stainless Steel: #4 satin polish

### SD-6000 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Weight per Door	
inches	mm	lbs.	kg.
12 x 12	305 x 305	22	10
16 X 16	406 X 406	30	13.8
18 x 18	457 x 457	46	21
24 x 24	610 x 610	70	31.8
24 x 36	610 x 914	90	41
36 X 36	914 X 914	120	54.4

Wall or ceiling opening is normal door size plus +5/8" (16mm)  
For detailed specifications see submittal sheet



Detention Lock with Paracentric Key

